



Features

- Industrial-grade 18.5" FHD LCD panel with 50k backlight lifetime
- True-flat touchscreen with multi-touch projected capacitive control
- Intel® Celeron® J6412 quad-core 2.0 GHz processor
- 1 x DDR4 SDRAM, max.32GB, 1 x M.2 2280 / 1 x 2.5" SATA SSD
- SP13 I/O ports : 2 x LAN / 2 x USB / 1 x COM
- Full device IP66/IP69K with Strong aluminum alloy casing
- Support TPM2.0 hardware security
- Wide Operating Temperature -20°C to 70°C
- 9V to 36V DC Wide Range Power Input , Supporting OVP / OCP / RPP

Specifications

System	
CPU	Intel® Elkhart Lake Celeron J6412 Quad-core 2.0GHz
L2 Cache	1.5MB
TDP	10W
System Chipset	Integrated with Intel® SoC
Memory	1 x DDR4L 3200MHz 4GB, MAX 32GB
Harddisk	1 x M.2 120G SSD (250G / 500G / 2TB SSD) / 1 x 2.5" SATA
Graphics	Intel® UHD Graphics for 10th Gen Intel® Processors
Network	Intel® 226-V GbE LAN
Audio	Realtek ALC897 Audio controller
TPM	TPM 2.0
Watchdog Timer	Software Programmable Supports 1~255 sec. System Reset
Operation System	Windows 10 / 11 , Linux, Ubuntu
I/O	
VIDEO	1 x H-DMI (Optional)
Ethernet	2 x SP13 Waterproof Giga LAN RJ45 Connector
USB	2 x SP13 Waterproof Connector For USB2.0
COM	1 x SP13 Waterproof Connector For COM
Wireless Network	Optional (WiFi / Bluetooth / 4G / 5G)
Other I/O Interface	1 x Power Switch
Expansion	
M.2	1*M.2 (Key-E, 2230, PCIe+USB, Wifi+BT)
	1*M.2 (Key-B, 2242/3052, PCIe/ USB 3.0+USB2.0, 4G/5G)
	1*M.2 (Key-M, 2280,NVMe/ SATA, SSD)
SIM Socket	1x SIM Socket
Display	
LCD Size	18.5" (16:9)
Resolution	1920 x 1080 (FHD)
Brightness (cd/m ²)	350 cd/m ²
Contrast Ratio	1200:1
Backlight MTBF	50,000 hrs (LED Backlight)
Viewing Angle	85 / 85 / 85 / 85 (CR≥10) (L / R / U / D)
Touch screen	
Touch Type	10 point PCAP
Surface Hardness	≥7H

Power	
Power Input	1 x SP13 Waterproof Connector For 9V~36V DC
Power Mode	Support AT, ATX Mode
Power Protection	OVP (Over Voltage Protection) OCP (Over Current Protection) RPP (Reverse Polarity Protection)
Power Consumption	≤45W
Physical	
Material	Aluminum Alloy Shell
Mounting	Stand / Wall / VESA
Dimension (W x H x D)	464 x 285 x 45 mm
Packing Size	500 x 180 x 450 mm
Weight (Net)	7.5 KG
Environment	
Operating Temperature	-20~70°C (-4~158°F)
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	IP66 / IP69K
EMC	CE, FCC , Class A , ROHS

Dimension & I/O

I / O Definition:

A: Power Button	B: Breather Valve
C: COM (optional)	D: USB (optional)
E: USB (optional)	F: LAN (optional)
G: LAN (optional)	H: DC 9V~36V

Product Dimensions: 464 x 284.6 x 45 mm (18.27 x 11.2 x 1.77 in)

Ordering info

Available models	Description
WPC-C185WAC	18.5" Fanless Waterproof Industrial PC Intel® Celeron J6412 2.0GHz Processor With Capcice touch

Packing list

1 x Standard product
1 x 60W PSU (Power Supply)
2 x SP13 Waterproof USB Cable 1.5M
1 x SP13 Waterproof COM Cable 1.5M
2 x SP13 Waterproof LAN Cable 1.5M
1 x Waterproof HDMI Cable 1.5M
1 x CD-ROM